

**Declaration of Performance**

**Interlyte 7.3N Masonry Unit – Standard and Close Textured**

1. Product Type: **75 – 140mm Solid Interlyte 7.3N/mm<sup>2</sup>**
2. Identification: **Solid Interlyte 7.3**
3. Intended use: **in walls, columns, partitions and, 100mm Solid only, floor beams**
4. Manufacturer: **Interfuse Limited, 80 High Street, Syston. LE7 1GS**

**Tel: 0116 2609666 e-mail: iancollard@interfuseblocks.com**

5. AVCP: **System 4**

6. ETA: **Not Relevant**

7. Declaration of performance

Essential Characteristics		Performance	Designated Standard
<b>Dimensions</b>	Length	440mm	BS EN 771-3:2011
	Width	75mm, 90mm, 100mm or 140mm	
	Height	215mm	
	Tolerance category	D1	
	Shape and features	NPD	
	Group according to EN1996-1-1 (EC6)	Group 1	
<b>Compressive strength</b>	Mean comp' strength	7.3N	
	Direction of load	Perpendicular to bed face	
	Unit category	Category II	
<b>Dimensional stability</b>		<0.5mm/m	
<b>Bond strength</b>	Shear bond strength	0.15N/mm <sup>2</sup>	
	Flexural bond strength	NPD	
<b>Reaction to fire</b>		Euro Class A1	
<b>Water absorption</b>		NPD	
<b>Water vapour permeability</b>		5/15 (tabulated value)	
<b>Gross Density</b>		Solid – 1450kg/m <sup>3</sup>	
<b>Thermal resistance</b>		0.38 λ10, dry, unit (tabulated value)	
<b>Durability against freeze/thaw</b>		Not to be left exposed	
<b>Dangerous substances</b>		NPD	

This declaration of performance is issued under the sole responsibility of the manufacturer identified in 4. Signed on behalf of the Interfuse Ltd:



**D Jelley**  
**Managing Director.**  
 Interfuse 2024